

DOWNLIGHT



DORIAN AP

| | | |
|-----------|------------|--------------|
| IP | CRI | AC220 |
| 20 | 90 | -240V |



DORIAN AP DOWNLIGHT

Surface-mounted LED downlight for installation in shops, showrooms, museums, corridors, reception rooms, offices ...

Luminaire housing with aluminium extruded section, painted

Energy-saving, long-life LED surface-mounted downlight

High luminous flux of luminaire

Alternative for conventional halogen spotlights

Purged design

Highly efficient aluminium reflector, wide-beam



luxio
L I G H T I N G

www.luxio-lighting.com

References

| Reference | Led Power | Luminous flux | CCT/K | OPTICS | IP Rating | Dimensions | Adjustable |
|----------------|-----------|---------------|-------------|-------------|-----------|------------|--------------|
| LX-DL-0321-LED | 10W | 440Lm | 3000K/4000K | 6° | IP20 | Ø52*150mm | 0-90°/0-361° |
| LX-DL-0322-LED | 10W | 770Lm | | 15°/22°/30° | | Ø70*140mm | |
| LX-DL-0331-LED | 21W | 1447Lm | | 15°/24°/36° | | Ø90*140mm | |
| LX-DL-0341-LED | 28W | 2120Lm | | | | | |

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

OPTICS

LX-DL-0321-LED



6°

LX-DL-0322-LED



15°

22°

30°

LX-DL-0331-LED/LX-DL-0341-LED



15°

24°

36°

Optional adapter




Honeycomb




Spread Lens

Dimensions


LX-DL-0321-LED



LX-DL-0322-LED



LX-DL-0331-LED



LX-DL-0341-LED

