


DOWNLIGHT



SANY W



SANY W

COB downlight for providing high performance general lighting and accent lighting
Multiple square sizes for different applications

Excellent glare control (UGR<19)

Optics : Reflector & lens

Material : Aluminum Frame & Heatsink

Applications : Hotels and restaurants, Shopping centers and retail stores , Offices and
Offices and administration buildings, Schools and Libraries.

Large architectural structures



References

Reference	Led Power	Luminous flux	CCT/K	OPTICS	IP Rating	Dimensions	Adjustable
LX-DL-W11104	8W	579lm	2700K/3000K/4000K	24°/40°	IP20	99*99*108mm	350°/30°
	12W	785lm					
LX-DL-W11504	15W	1136lm					
	20W	1523lm					
	25W	1865lm					
LX-DL-W11954	25W	2086lm		16°/26°/40°/60°		IP20	
	30W	2503lm					
	36W	2763lm	182*182*172mm				
	40W	3025lm					

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

OPTICS

LX-DL-11104



24°

40°

LX-DL-11504 / LX-DL-11954



16°

26°


40°

60°


Dimensions



LX-DL-W11104



LX-DL-W11504



LX-DL-W11954

