

WALL LIGHT

LX-WL-20



Wall Light

FRONT COVER	12# Die-casting aluminum LX-WL-20-1-6W : Made by hard chrome-plated stainless steel
HOUSING	12# Die-casting grey powder coated aluminum T=60-80µm. Adhesion of ISO class 1/ASTM class 4B
LIGHT WINDOW	UVstop & Fireproof PC T=3mm
CABLE CABLE	IP68 PG-9 PA66
GASKET	Molding shaped silicone seal
RECESSED SLEEVE	PC/ABS ALLOYS
LED DRIVER	Constant Voltage Input, Constant Current Output
OPERATING TEMPERATURE	-20°C-40°C
POWER CABLE	H05RN-F 2×1.0mm² L=0.5m (low voltage) H05RN-F 3×1.0mm² L=0.5m (high voltage)
DIMMABLE SURPPORT	Triac • PWM • 1-10V • Dali (Please refer to p.333 to see more option and specification)



References

Reference	Led Power	Input Voltage	Led Quantity	Luminous flux	CCT/K	IP Rating	Dimensions
LX-WL-20-6W	15×0.2W	DC24V AC120-240V	15pcs	104-113lm	2000K/3000K /6000K	IP65	L255×H76×W70mm
LX-WL-20-2-6W	54×0.07W		54pcs	44-47lm			L255×H76×W70mm
LX-WL-20-1-6W	54×0.07W		54pcs	130-150lm			L255×H76×W70mm
LX-WL-20-3-6W	28×0.15W		28pcs	65-82lm			L255×H76×W80.5mm

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Housing color option

Basic



Sanded Dark Grey
KAP 7037

Secondary



Sanded Black
RAL 9005



Silver Grey
KAP 9022

Features




- The above picture – the supporting plate "A1" and "A2" are used for preventing deformation of the sleeve during the construction installation process.
- Please remove the supporting plate "A1" and "A2" from the mountingsleeve before the lamp installation.


Dimensions




LX-WL-20-6W



LX-WL-20-2-6W



LX-WL-20-1-6W



LX-WL-20-3-6W

