

WALL LIGHT

LX-WL-41-2

IP 65	IK 05/06/10	DC24V AC120-240V	TRIAC	PMW	1-10V	WALL
2 YEAR WARRANTY	NICHIA	CE	RoHS	50000h		

Wall Light

HOUSING MATERIAL Extruded aluminum alloy #6063

PAINTING Powder coating, T=60-80µm.
Adhesion of ISO class 1/ASTM class 4B

REFLECTOR Optical reflector, efficiency ≥ 85%

OPERATING TEMPERATURE -20°C-40°C

POWER CABLE H05RN-F 2×1.0mm² L=0.3m (low voltage)
H05RN-F 3×1.0mm² L=0.3m (high voltage)



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Led Power	Luminous flux	Input Voltage	CCT/K	IK Rating	IP Rating	Optics	Light direction	Dimensions
LX-WL-41-2	1*4.5W	282lm	DC24V/ AC120-240V	3000K/6000K	IK05	IP65	15°/24°/38°	Single side	Ø60*H130mm
	1*10W	1170-1335lm			IK10		15°/24°/38°/60°		Ø80*H146mm
	1*18W	1432-1684lm					12°/22°/35°/55°		Ø100*H195.5mm
	1*25W	2412-2615lm					10°/22°/38°		Ø130*H244mm
	1*40W	3808-4112lm			IK06		12°/25°/38°		Ø160*H284mm

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Housing color option

Basic



Sanded Dark Grey
KAP 7037

Secondary




Sanded Black
RAL 9005




Silver Grey
KAP 9022

Dimensions


LX-WL-41-2-4.5W





LX-WL-41-2-10W



LX-WL-41-2-18W



LX-WL-41-2-25W



LX-WL-41-2-40W

