

WALL LIGHT



LX-WL-41F-2



Wall Light

HOUSING 12# Die-casting dark grey powder coated aluminum.
T=60-80µm. Adhesion of ISO class 1/ASTM class 4B

LIGHT WINDOW Glass T=3mm

GASKET Tooling shaped seal

LED DRIVER Main voltage 100V-240V driver inside builded

OPERATING TEMPERATURE -20°C-40°C

POWER CABLE H05RN-F 2×1.0mm² L=0.3m (low voltage)
H05RN-F 3×1.0mm² L=0.3m (high voltage)



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Led Power	Luminous flux	Input Voltage	CCT/K	IK Rating	IP Rating	Optics	Light direction	Dimensions
LX-WL-41F-2	1*10W	504lm	AC240V	3000K/6000K	IK06	IP65	6°	One side	Ø80*H159mm
	2*8W	2*297lm						Two side	Ø80*H248mm

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Housing color option

Basic



Sanded Dark Grey
KAP 7037

Secondary




Sanded Black
RAL 9005



Silver Grey
KAP 9022

Dimensions

LX-WL-41F-2-10W



LX-WL-41F-2-16W

