

WALL LIGHT



LX-WL-43-2

IP
65

IK
06

DC24V
AC120-240V

TRIAC

PMW

1-10V



NICHIA

CE

RoHS

50000h

Wall Light

HOUSING MATERIAL Extruded aluminum alloy #6063

PAINTING Powder coating, T=60~80µm.
Adhesion of ISO CLASS 1/astm class 4B

REDLECTOR Optical reflector, efficiency≥85%

POWER CABLE H05RN-F 2×1.0mm² L=0.3m (low voltage)
H05RN-F 3×1.0mm² L=0.3m (high voltage)

OPERATING TEMPERATURE -20°C-40°C



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Led Power	Luminous flux	Input Voltage	CCT/K	IK Rating	IP Rating	Optics	Dimensions
LX-WL-43-2	1*18W	2205lm	DC24V AC120-240V	3000K/6000K	IK06	IP65	15°/20°/25°/38°/55°	Ø130*H165mm
	1*30W	2851lm					15°/25°/36°/60°	Ø160*H185mm
	1*48W	4482lm					15°/25°/36°/60°	Ø200*H235mm

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Housing color option



Sanded Black
RAL 9005



Dark Grey
RAL 7037



Sanded White
RAL 9003

Accessories (Optional)

ANTI-GLARE LOUVER



LX-Mh074



LX-Mh072



LX-Mh066



LX-Mh073



LX-Mh071



LX-Mh065



Features





Safety hook



When wiring, the hook can be hung on the ceiling mount. When the wiring is completed, there is no need to remove the hook, which can be used as a safety protection when the lamp is removed.

Dimensions



LX-WL-43-2-18W



LX-WL-43-2-30W



LX-WL-43-2-48W



www.luxio-lighting.com