

WALL LIGHT

LX-WL-7CX0934-6W



Wall Light

HOUSING	12# Die-casting aluminum T=20-25µm. Adhesion of ISO class 1/ ASTM class 4B high temperature painting
FRONT COVER	12# Die-casting aluminum
LIGHT WINDOW	Glass=2mm UVstop & Fireproof PC=3mm
MOUNTING SLEEVE	ADC12# 151#
LIGHT SOURCE	NICHIA
LED DRIVER	Constant Voltage Input, Constant Current Output
OPERATING TEMPERATURE	-20°C-40°C
POWER CABLE	H05RN-F 3X1.0mm² L=0.3m (high voltage)
DIMMABLE SUPPORT	Triac PWM 1-10V Dali



www.luxio-lighting.com

References

Reference	Led Power	Input Voltage	Led Quantity	Luminous flux	CCT/K	IP Rating	Dimensions
LX-WL-7CX0934-6W	9×0.5W	DC24V AC120-240V	9pcs	142lm	2000K/3000K /6000K	IP65	L120×H120×W76mm

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Housing color option

Basic



Sanded Dark Grey
KAP 7037

Secondary



Sanded Black
RAL 9005



Silver Grey
KAP 9022

Dimensions

