

INGROUND



LX-IG-67A



Inground

- FRONT COVER Hard chromeplated stainless steel SUS 316#
- HOUSING 12# Die-casting dark grey powder coated aluminum T=60-80µm. Adhesion of ISO class 1/ASTM class 4B
- LIGHT WINDOW Tempered frosted step glass, T=7mm
- GASKET H05RN-F 2×1.0mm² L=0.5m
- POWER CABLE IP68 PG-9 PA66
- LED TYPE OSRAM
- GLASS PRESSURE CAPACITY Full area=1,106kgs
- OPERATING TEMPERATURE -20°C~40°C




References

Reference	Led Power	Luminous flux	Input Voltage	CCT/K	IK Rating	IP Rating	Optics	Dimensions
LX-IG-67A	1*2W	140-155lm	AC100-240V DC24V	2000K/3000K/6000K	IK08	IP67	20°/30°/45°/60°	Ø58*W43mm

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Honeycomb Louver (Option)



Louver Mh021

- Optional Accessory Honeycomb Louver
- The measured luminous flux data does not contain the honeycomb cover, and the data containing the honeycomb cover is reduced by 20 to 30%.

Water Proof Solution

- A Water stopper(Included)
- B Water proof connector IP67(Optional)



Low Voltage



High Voltage

Installation Diagram

Low Voltage



A: Minimum space for external driver is 20mm.

High Voltage



A: Minimum space for external driver is 48mm.

B: IP67 120V/240V/24V&RGB 24V external high voltage driver.

Dimensions

