

TUBE

LX-TU-T1200-10W

| | | | | | | |
|-----------------|-----------------|-------------------|--------------------|-----------------|-----------------|-------------------|
| IP 65 | IK 08 | CRI >80 | PF ≥ 0.9 | SDCM ≤ 6 | CLASS II | AC220-240V |
|-----------------|-----------------|-------------------|--------------------|-----------------|-----------------|-------------------|

| | | | |
|---------------------------|-----------|-------------|---------------|
| 3 YEAR WARRANTY | CE | RoHS | 30000h |
|---------------------------|-----------|-------------|---------------|

TREE PROOF

Material / Finish (RAL) : PC

Installation Method : Ceiling mounted/Suspension mounted

LED Chips : SMD2835/1W

Beam Angle : Open area-120°

Inrush Current : ≤40A & 220us@230Vac

Running Current : 110±5%

Glow Wire Testing (TP rating) : 650°

Working Temps : -20°C~+45°C



luxio
L I G H T I N G

www.luxio-lighting.com

References

| Reference | Led Power | Luminous flux | CCT/K | OPTICS | IP Rating | Dimensions |
|-----------------|-----------|---------------|------------------------|--------|-----------|---------------------|
| LX-TU-T1200-10W | 10W | 1300lm | 3000k/4000k/6500K /CCT | 120° | IP65 | L1200 x W87 x H74mm |

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Dimensions

