

# TUBE

## LX-TU-T1500-24W

<b>IP</b> 65	<b>IK</b> 08	<b>CRI</b> >80	<b>PF</b> ≥ 0.9	<b>SDCM</b> ≤ 6	<b>CLASS II</b>	<b>AC220-240V</b>
-----------------	-----------------	-------------------	--------------------	-----------------	-----------------	-------------------

<b>3</b> YEAR WARRANTY	<b>CE</b>	<b>RoHS</b>	<b>30000h</b>
---------------------------	-----------	-------------	---------------

### TREE PROOF

Material / Finish (RAL) : PC

Installation Method : Ceiling mounted/Suspension mounted

LED Chips : SMD2835/1W

Beam Angle : Open area-120°

Inrush Current : ≤40A & 220us@230Vac

Running Current : 110±5%

Glow Wire Testing (TP rating) : 650°

Working Temps : -20°C~+45°C



**luxio**  
L I G H T I N G

[www.luxio-lighting.com](http://www.luxio-lighting.com)

## References

Reference	Led Power	Luminous flux	CCT/K	OPTICS	IP Rating	Dimensions
LX-TU-T1500-24W	24W	2600lm	3000k/4000k/6500K /CCT	120°	IP65	L1500 x W87 x H74mm

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

## Dimensions

