


# DOWNLIGHT



## CORN R



Optional



### CORN R

Description : Fixed lighting design, Corn recessed downlight can help you better show the sense of space, saves the trouble of adjusting lamps.

Applications : Large architectures, Hotels, Bars, Restaurants, Shopping centers, Retail stores, Showrooms, Galleries, Offices and Administration buildings.

Material : aluminum

COLOUR(housing) : Black/White

COLOUR(reflector) : Black/Gold/White

Colour temperature : 2700K, 3000K, 4000K, 5000K



## References

Reference	Led Power	Luminous flux	CCT/K	OPTICS	IP Rating	Dimensions	Adjustable
LX-DL-11011-2	8W	605-792lm	2700K	15°/24°/38°/60°/15°x40°	IP20	Ø101*114mm	—
		638-812lm	3000K				
	12W	836-1010lm	2700K				
		924-1047lm	3000K				
	15W	998-1108lm	2700K				
		1048-1147lm	3000K				
LX-DL-11361-2	15W	1029-1358lm	2700K	15°(exc.36W)/24°/38°/60°/ 15°x40°(exc.36W)	IP20	Ø136*145mm	—
		1064-1387lm	3000K				
	20W	1407-1839lm	2700K				
		1633-1880lm	3000K				
	25W	1654-2167lm	2700K				
		1883-2213lm	3000K				
	30W	1905-2421lm	2700K				
		2104-2517lm	3000K				
	36W	2277-2540lm	2700K				
		2522-2831lm	3000K				
LX-DL-11012-2	8W	637-792lm	2700K	15°/24°/38°/60°/15°x40°	IP20	Ø101*105mm	—
		658-812lm	3000K				
	12W	872-1010lm	2700K				
		910-1047lm	3000K				
	15W	985-1093lm	2700K				
		1005-1147lm	3000K				
LX-DL-11362-2	15W	1026-1358lm	2700K	15°(exc.36W)/24°/38°/60°/ 15°x40°(exc.36W)	IP20	Ø136*130mm	°30/350°
		1056-1387lm	3000K				
	20W	1544-1839lm	2700K				
		1617-1880lm	3000K				
	25W	1824-2167lm	2700K				
		1869-2213lm	3000K				
	30W	2083-2421lm	2700K				
		2099-2517lm	3000K				
	36W	2277-2540lm	2700K				
		2522-2831lm	3000K				


Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .


# Dimensions




LX-DL-11011-2



LX-DL-11361-2



LX-DL-11012-2



LX-DL-11362-2

