

GARDEN LIGHT



LX-FL-B3B-GHI

IP 66	IK 07	DC24V/ AC120-240V	TRIAC	PMW	1-10V	HALT
----------	----------	----------------------	-------	-----	-------	------



HOUSING 12# Die-casting dark grey powder coated aluminum. T=60-80µm. Adhesion of ISO class 1/ASTM class 4B

LENS All-in-one optical lens, efficiency≥85%

LIGHT WINDOW Tempered glass. T=4mm

CABLE GLAND IP68 PG-9 PA66

GASKET Tooling shaped seal

BRACKET Powder coated aluminum

POWER CABLE H05RN-F 2×1.0mm² L=2.0m (low voltage)
H05RN-F 3×1.0mm² L=2.0m (high voltage)



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Led Power	Led Quantity	Input Voltage	Luminous flux	CCT/K	OPTICS	IP Rating	Dimensions
LX-FL-B3B-GHI	8W	1pc	DC24V/ AC120-240V	326lm	3000K/4000K/5700K CCT	18°/28°/38°	IP66	Ø90*W102*H124mm
	12W			1263lm		15°/24°/38°		Ø130*W152*H180mm
	18W			2101lm		12°/24°/36°/60°		Ø160*W143*H194mm

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Water proof solution



Accessories (Optional)

PC/ABS alloys SPIKE




- 17B: LX-FL-B3B-GHI-8W
LX-FL-B3B-GHI-12W
LX-FL-B3B-GHI-18W
- More information
please refer to p.93

STAINLESS STEEL SPIKE




- 13B: LX-FL-B3B-GHI-8W
LX-FL-B3B-GHI-12W
LX-FL-B3B-GHI-18W
- More information
please refer to p.94

MOUNTING BASE



- S002: LX-FL-B3B-GHI-8W
LX-FL-B3B-GHI-12W
S003: LX-FL-B3B-GHI-18W


HONEYCOMB LOUVER




- Mh017: LX-FL-B3B-GHI-8W
Mh050: LX-FL-B3B-GHI-12W
Mh051: LX-FL-B3B-GHI-18W
- The measured luminous flux
data does not contain the
honeycomb, and the data
containing is reduced 20 to
30%.

Dimensions

LX-FL-B3B-GHI-8W



LX-FL-B3B-GHI-12W



LX-FL-B3B-GHI-18W

