

GARDEN LIGHT



LX-G-S0126

IP 66	IK 06	DC24V AC120-240V	TRIAC	PMW	1-10V	RA1
----------	----------	---------------------	-------	-----	-------	-----

3 YEAR WARRANTY	NICHIA	CE	RoHS	50000h
-----------------------	--------	----	------	--------

Garden Light

HOUSING	12# Die-casting dark grey powder coated aluminum. T=60-80µm.Adhesion of ISO class 1/ASTM class 4B
LIGHT WINDOW	Tempered glass.T=4mm
GASKET	Tooling shaped seal
LED	Nichia
LED DRIVER	Constant Voltage Input, Constant Current Output
LENS/REFLECTOR	Optical lens,efficiency≥85%
OPERATING TEMPERATURE	-20 C ~40 C
POWER CABLE	H05RN-F 2×1.0mm ² L=2.0m(low voltage) H05RN-F 3×1.0mm ² L=2.0m(high voltage)



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Led Power	Led Quantity	Input Voltage	Luminous flux	CCT/K	OPTICS	IP Rating	Dimensions
LX-G-S0126	3W	1pc	DC24V/ AC120-240V	274-305lm	3000K/6000K	9°/15°/20°/30°/45°	IP66	Ø45*W96*H300mm
	6W			667-740lm		20°/36°		Ø60*W120*H312mm
	10W			1200-1315lm		20°/36°		Ø68*W139*H330mm
	20W			2071-2200lm		15°/25°/38°		Ø95*W165*H435mm

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Housing color option

Basic



Dark Grey
KAP 7037

Secondary




Silver Grey
KAP 9022




Sanded Black
RAL 9005

Dimensions



LX-FL-S0126-3W




LX-FL-S0126-6W



LX-FL-S0126-10W




LX-FL-S0126-20W




Accessories (Optional)

STAINLESS STEEL SPIKE




- 12A: LX-G-S0126-3W
LX-G-S0126-6W
LX-G-S0126-10W
13A: LX-G-S0126-20W
- More information please refer to p.93

BEVEL CUT HOOD





- A3009: LX-G-S0126-3W
A3010: LX-G-S0126-6W
A3011: LX-G-S0128-10W
A3009: LX-G-S0126-20W

TREE POLE STRAP



- D003: LX-G-S0126-3W
LX-G-S0126-6W
D002: LX-G-S0126-10W
LX-G-S0126-20W
- More information please refer to p.94

HONEYCOMB LOUVER



- Mh024: LX-G-S0126-3W
Mh025: LX-G-S0126-6W
Mh026: LX-G-S0126-10W
Mh027: LX-G-S0126-20W
- The measured luminous flux data does not contain the honeycomb, and the data containing is reduced 20 to 30%.

Overview

Water proof solution

