


# DOWNLIGHT

## MAGNETIC SPOTLIGHT RS



### MAGNETIC SPOTLIGHT R/S

Magnetic suction installation. The grille design of completely hidden lamp makes the light softer, so you will feel more comfortable in the space.

Tunable White allows the colour temperature to be continuously adjusted from warm light to cool light.

Applications : Showrooms, Restaurants, Star-rated Hotels, Villas, Residential buildings, etc.

Physical : Aluminum

Colour(housing) : black

Colour(reflector) : Black

Colour temperature : 2700K, 3000K, 4000K, 5000K



## References

| Reference               | Led Power | Luminous flux | CCT/K | OPTICS      | IP Rating | Dimensions                     |      |                                |      |                                |
|-------------------------|-----------|---------------|-------|-------------|-----------|--------------------------------|------|--------------------------------|------|--------------------------------|
| LX-DL-G201 / LX-DL-G203 | 1W        | 47-72lm       | 2700K | 15°/24°/33° | IP20      | (20*20*45mm)/<br>(250*24*37mm) |      |                                |      |                                |
|                         |           | 48-78lm       | 3000K |             |           | (20*20*45mm)/<br>(250*24*37mm) |      |                                |      |                                |
|                         | 3W        | 79-124lm      | 2700K |             |           | (20*20*45mm)/<br>(250*24*37mm) |      |                                |      |                                |
|                         |           | 82-134lm      | 3000K |             |           | (20*20*45mm)/<br>(250*24*37mm) |      |                                |      |                                |
| LX-DL-G202 / LX-DL-G204 | 2*1W      | 94-144lm      | 2700K |             |           | 15°/24°/33°                    | IP20 | (20*20*45mm)/<br>(250*24*37mm) |      |                                |
|                         |           | 96-156lm      | 3000K |             |           |                                |      | (20*20*45mm)/<br>(250*24*37mm) |      |                                |
|                         | 2*3W      | 158-248lm     | 2700K |             |           |                                |      | (20*20*45mm)/<br>(250*24*37mm) |      |                                |
|                         |           | 164-268lm     | 3000K |             |           |                                |      | (20*20*45mm)/<br>(250*24*37mm) |      |                                |
| LX-DL-G205 / LX-DL-G206 | 3*1W      | 141-216lm     | 2700K |             |           |                                |      | 15°/24°/33°                    | IP20 | (20*20*45mm)/<br>(250*24*37mm) |
|                         |           | 144-234lm     | 3000K |             |           |                                |      |                                |      | (20*20*45mm)/<br>(250*24*37mm) |
|                         | 3*3W      | 237-372lm     | 2700K |             |           |                                |      |                                |      | (20*20*45mm)/<br>(250*24*37mm) |
|                         |           | 246-402lm     | 3000K |             |           |                                |      |                                |      | (20*20*45mm)/<br>(250*24*37mm) |

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

## Features



## Dimensions

