

UNDERWATER

LX-IG-129



HOUSING Hard chromeplated molding shaped stainless steel SUS 316#

LIGHT WINDOW Step tempered glass. T=10mm

CABLE GLAND IP68 PG-11 copper with nickel-coated

GASKET Silicone gasket

PCB Excellent heat conductivity aluminum. coefficient of heat Conductivity ≥ 2.0 w/mk

LED DRIVER Constant Voltage Input, Constant Current Output

APPLICATION ENVIRONMENT Temperature of water between -20°C~40°C less than 1 meter depth

BUILT-IN OVERHEAT SENSOR SYSTEM Automatic Shutdown at 75°C

POWER CABLE H07RN-F 2X1.0mm² L=3.0m

DIMMABLE SUPPORT Triac PWM 1-10V Dali




References

Reference	Led Power	Led Quantity	Input Voltage	Luminous flux	CCT/K	OPTICS	IP Rating	Dimensions
LX-IG-129	12x2W	12pcs	DC24V	1610-2067lm	2000K/3000K /6000K	20°/25°/30°/35°/45°	IP68	Ø200*W65mm


Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Water proof solution



Central Ejective



Water jet pipe G1/2"taper

- A** Water stopper(Included)
- B** Water proof connector IP68(Option)



Dimensions

