

UNDERWATER

LX-IG-146



- FRONT COVER & HOUSING** Hard chromeplated molding shaped stainless steel SUS 316L#
- LIGHT WINDOW** Step tempered glass.T=5mm
- GASKET** EPDM gasket
- LENS** Optical lens,efficiency≥85%
- CABLE GLAND** IP68 PG-11 copper with nickel-coated
- PCB** Excellent heat conductivity aluminum.coefficient of heat Conductivity≥2.0w/mk
- LED DRIVER** Constant Voltage Input,Constant Current Output
- POWER CABLE** H07RN-F 2X1.0mm² L=3.0m
- APPLICATION ENVIRONMENT** Temperature of water between -20°C~40°C less than 1 meter depth
- BUILT-IN OVERHEAT SENSOR SYSTEM** Automatic Shutdown at 75°C



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Led Power	Led Quantity	Input Voltage	Luminous flux	CCT/K	OPTICS	IP Rating	Dimensions
LX-IG-146	3x3W	3pcs	DC24V	662-789lm	2000K/3000K /6000K	8°/13°/25°/30°	IP68	L326*H67*W47mm
	6x3W	6pcs		1324-1578lm				L178*H67*W47mm

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Water proof solution

- A** Water stopper(Included)
- B** Water proof connector IP68(Optional)



LX-IG-146-9W




LX-IG-146-18W



Tripod-Optional Accessory


LX-IG-146-9W

5002



LX-IG-146-18W

5003



Dimensions

