

UNDERWATER

LX-IG-AB65



HOUSING Hard chromeplated molding shaped stainless steel SUS 316#

LIGHT WINDOW Step tempered glass. T=8mm

CABLE GLAND IP68 PG-11 copper with nickel-coated

GASKET Silicone gasket

PCB Excellent heat conductivity aluminum. coefficient of heat Conductivity ≥ 2.0 w/mk

LED DRIVER Constant Voltage Input, Constant Current Output

APPLICATION ENVIRONMENT Temperature of water between -20°C ~ 40°C less than 1 meter depth

BUILT-IN OVERHEAT SENSOR SYSTEM Automatic Shutdown at 75°C

POWER CABLE H07RN-F 2X1.0mm² L=3.0m

DIMMABLE SUPPORT Triac PWM 1-10V Dali



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Led Power	Led Quantity	Input Voltage	Luminous flux	CCT/K	OPTICS	IP Rating	Dimensions
LX-IG-A65	6x1.5W	6pcs	DC24V	825lm	2000K/3000K /6000K	10°/15°/200°/30°	IP68	Ø128*W65mm
LX-IG-B65								Ø116*W65mm

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Water proof solution

- A** Water stopper(Included)
- B** Water proof connector IP68(OPTION)



Dimensions

