

MAGNETIC TRACK LIGHT



LX-DL-M20NK-27

IP 20	CRI >90	SDCM <3 Step	DC48V
-----------------	-------------------	------------------------	--------------

		CASAMBI
--	--	----------------

	CE	RoHS	50000h
--	-----------	-------------	---------------

- Material: Silicone Neon
- Coating: Black
- Length: 1000mm/1500mm/5000mm optional
- CCT: 2700/3000/3500/4000K optional
- Light efficiency: 45 lm/W
- Lighting direction: downward
- Application: Indoor



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Input Voltage	Type Power	Max Power	Luminous flux	CRI	CCT/K	Beam Angle	IP Rating	Length
LX-DL-M20NK-27	48VDC	10W	11W	410lm	>90	2700K	110°	IP20	1000mm
				420lm		3000K			
				430lm		3500K			
				450lm		4000K			
		14W	15.4W	575lm		2700K			1500mm
				585lm		3000K			
				605lm		3500K			
				630lm		4000K			
		48W	52.8W	1975lm		2700K			5000mm
				2010lm		3000K			
				2065lm		3500K			
				2160lm		4000K			

1. The output data is based on the testing result of Ra90,4000k luminaires;
2. The tolerance of output data can be vary up to 10%;
3. The output data is typical value.

Dimensions

