

PROFIL LIGHT



LX-PL-LR3735

24V	CRI >80/95	PF >0.9	IP 20
-----	---------------	------------	----------



LX-PL-LR3735

- 35mm luminous surface, rimless recessed design, integrated into architecture.
- AL6063-T5 aluminum profile with high-quality surface treatment.
- Indirect lighting design integrates architectural and lighting effects.



luxio
L I G H T I N G

www.luxio-lighting.com

Standard Configuration

Picture	Item	Parameter	Model
	Profile	Profile weight: 2.25kg/2.5m Size: L2500*W99*H35mm Material: AL6063-T5 Surface processing: Anodizing	/
	End caps	Size: L59.8*W35*H2mm Material: AL	LX-LR3735

Optional Accessories

Picture	Item	Parameter	Model
	Flexible strip LX-ST-D8168-24V -10mm	Material: FPC,CCT:1900/2300/2700/3000/3500/4000/5000 /6000K; CRI > 90/>95; Voltage: 24V; Power: 16.2W/m; Lumen: 1860Lm/m; Width: 10mm; Minimum cutting unit: 7LEDs/42mm;	LX-ST-D8168-24V -10mm
	Screw	Size: M3.5*40mm Material: Carbon steel	LX-CL-01

Dimensions

