

STREET LIGHT



LX-SL-DONA

IP	IK	PF	CRI	8/6KV	DC24V /AC120-240V
66	08	>0.95	>70/>80		



LUXEON

Driver

PHILIPS



CB

RoHS

100.000hrs

STREET LIGHT

Housing accommodates up to 5 LED lighting units (LED Board: 32 / 48 / 64 / 80 LED)

Body : Corrosion resistant aluminum bowl

Surface : Electrostatic powder paint

Connectors : Stainless steel (304 grade)

Surface : Electrostatic powder paint

Gasket : EPDM Gasket (Hardness value A 20-25)

Lens / Reflector : High optical efficiency PMMA lens

Glass / Diffuser : Tempered safety glass

Current feed : 200 mA-1500 mA, depending on ambient temperature

Electronic operating device with DALI interface, 1-10 V or stand-alone programming

Various light distributions for area, high bay, street or walkway lighting

Lens made from PMMA, with aluminum support plate Cover in single-pane safety glass

Die-cast aluminum housing, pole adapter made of aluminum, swivels from 0 to 90° in 5° increments, for pole \varnothing 60 mm

Finish: polyester



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Led Power	Input Voltage	Luminous flux	CCT/K	IP Rating	Weight	Pole Top	Pole Height	Dimensions
LX-SL-DONA	30W	DC24V / AC100-240V	3600Lm	3000K/4000K /5000K	IP66	9 kg	60mm	3000-5000mm	L650*H207* W382mm
	40W		4800Lm					4000-6000mm	
	60W		7200Lm					5000-8000mm	
	80W		9600Lm					6000-10000mm	
	120W		14400Lm					8000-12000mm	

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Features

Models



Single

Double



Dimension

