

STREET LIGHT



LX-SL-LION-M

IP	IK	CRI	PF	AC220-240V	10KV	1-10V	DALI
66	09	>70	>0.95				

5	CE	CB	RoHS	100 000hrs	

LED street light LX-SL-LION-M

- Application : Roads, Streets, Highways, Bridges Parking lots, Park & Garden Pedestrian Crosses, Urban Areas, Roundabouts
- Housing Material : Alluminum alloy
- Cable : 3x1mm²
- Electrical Protection : I-II
- RAL Code : 7016
- Mounting Type : Pole
- Light Source : Mid / High Power LED
- Lens : PMMA
- Diffuser : Tempered Glass
- Beam Angle : Symmetric / Asymmetric
- Operating Temp.: -40°C ~+50°C
- External SPD applicable



luxio
L I G H T I N G

www.luxio-lighting.com

References

Reference	Led Power	Input Voltage	Luminous flux	Luminous Efficacy	CCT/K	IP Rating	Dimensions
LX-SL-LION-M	60W	AC220-240V	8220lm	137Lm/W	3000K/6500K	IP66	590*283*520mm
	80W		10960lm	137Lm/W			
	100W		13600lm	136Lm/W			
	120W		16200lm	135Lm/W			
	140W		18900lm	135Lm/W			
	150W		19800lm	132Lm/W			

Order code : Reference - Power - Luminous flux - CCT/K - Optic

Important : All the specification can be customized as per the project request .

Model Options



Dimensions(mm)

