


# DOWNLIGHT




## LX-DL-MT11G

<b>IP</b> 20	<b>CRI</b> 90	<b>DC48V</b>
-----------------	------------------	--------------



<b>5</b> YEAR WARRANTY	<b>CE</b>	<b>RoHS</b>	<b>50000h</b>
------------------------------	-----------	-------------	---------------

- Material : AL6063, spraying surface
- Coating : Matte Black (RAL9005)
- Size : 150\*15\*30mm / 300\*15\*30mm
- CCT : 2700K,3000K,4000K optional
- Beam angle : 30°
- Light efficiency : 65 LM/W
- Lighting direction : Downward
- Application : Indoor





## Luminaire Parameters

Version	Model	Length	Input Voltage (V)	Max. Current (A)	Type Power (W)	Max. Power (W)	CRI	Beam Angle	CCT	Lumen (LM)
Normal	LX-DL-MT11G	150mm	48VDC	0.115	5.0	5.5	>90	30°	2700K	310lm
									3000K	325lm
									4000K	345lm
		300mm		2700K	625lm					
				3000K	650lm					
				4000K	690lm					



Note:

1. The output data is based on the testing result of Ra90,3000k luminaires;
2. The tolerance of output data can be vary up to 10%;
3. The output data is typical value.

## Dimensions



## Optical Parameter




## Points to note

48V Power Supply



Total track Length ≤ 50M

48V Power Supply



























Max. Load ≤ 480W

Supplementary power supplies are needed beside the Spotlights module / Decorative module / Linear modular under below one conditions:

1. Load > 480W on the track
2. Total track length > 50M

## Accessories Information

Picture	Name	Model
	Trimless recessed track (13mm gypsum board)	LX-MT11-RX0
	Ceiling track	LX-MT11-SX0
	Pendant track	LX-MT11-HX0
	Pendant track	LX-MT11-SRX0
	ø1000mm 90° Ceiling curve track	LX-MS111090
	Rail energization box	LX-MT1101
	Horizontal corner power-on connectors	LX-MT1102
	Flexible energized connectors	LX-MT1103
	Rail energized connectors	LX-MT1104
	Pendant accessory	LX-MT1105
	Rail connectors	LX-MT1106
	End caps	LX-MT11-R-EC
	End caps	LX-MT11-S-EC
	End caps	LX-MT11-H-EC

Picture	Name	Model
	End caps	LX-MT11-SR-EC
	L-shaped (Inward)	LX-L90N-MS11
	L-shaped (Downward)	LX-L90-MS11
	L-shaped (Inward)	LX-L90N-MR11
	L-shaped (Downward)	LX-L90-MR11
	L-shaped (Inward)	LX-L90N-MH11
	L-shaped (Downward)	LX-L90-MH11
	L-shaped (Downward)	LX-L90-MSR11
	48V Constant Voltage Power supply(external)	LX-V48-XXXP
	48V Constant Voltage Power supply(build-in)	LX-100W48CG MICRO

Note:

1,Please refer to the accessory list table for detailed parameters.

2,Different tracks need to be used with corresponding accessories